
Granite Cobble Setts Footpath A110.07



DESIGN STATEMENT

Silver granite cobble setts can be used in designated shared zone areas to subtly alert users with textures and colour contrasts to the potential vehicles passing by.

In the overall design, granite cobble sett should be combined with smooth surface areas to allow access for pram and wheel chair.

APPLICABLE LOCATION

The treatment should be used in Brunswick, Coburg and Glenroy Activity Centre, mainly for shared zone design or as specified.

COUNCIL STANDARD DRAWING

N/A

CROSS REFERENCE DOCUMENT

- Coburg Streetscape Masterplan
- Brunswick Public Domain Manual
- AS 1428.1-1998 Supply of concrete

STANDARD SPECIFICATION

Dimension: Setts should be 100x100mm and should match silver highlight flagstones in the shared zone areas.

Grout: 10mm max. grouted joints colour to match setts. Grout finish level should be 5mm below the surface.

SUPPLIER

N/A

MAINTENANCE

Road Maintenance Unit: Replace Sections of footpaths when damaged.

Street Cleansing Unit: Cleaning will be undertaken as per current schedule.



GENERAL NOTES

1. **Mix:** Concrete for paver base shall be ready mix in accordance with relevant Australian Standard and shall have a 28 day compressive strength of 25Mpa minimum.
2. **Grade:** The cross fall of footpaths should not exceed 1 in 40.
3. **Joints:** expansion joints should be provided at max. 15 metres intervals.

A110.07 Granite Cobble Set Footpath

